

# PID FLOORS

HARDWOOD FLOORING SHOWROOMS

## 2 MM RECYCLED RUBBER UNDERLAYMENT



SKU RRUO2

### PERFORMANCE ATTRIBUTES

COMPATIBLE WITH MOST FLOOR FINISHES INCLUDING:  
HARDWOOD, ENGINEERED WOOD, LAMINATE, LVT, SHEET VINYL, AND CARPET

EASY INSTALLATION | MADE IN AMERICA FROM 92% RECYCLED RUBBER  
CAN BE THIN-SET TO TILE OR STONE (UP TO 12 MM) PER ASTM C627  
EARNS UP TO 9 LEED POINTS | COMPATIBLE WITH RADIANT HEATING SYSTEMS  
PROTECTS CERAMIC TILE, PORCELAIN, AND STONE FROM SUBSTRATE CRACKS  
RATED "LIGHT COMMERCIAL" BY THE TILE COUNCIL OF NORTH AMERICA  
PASSES VOC IAQ TEST (ASTM D5116)

### ACOUSTICS

YIELDS EXCEPTIONAL IMPACT SOUND INSULATION RESULTS, EVEN UNDER  
HARD SURFACE FLOORING FOR CONCRETE OR WOOD-FRAMED CONSTRUCTION.  
BACKED BY OVER 400 INDEPENDENT LAB-FILED TESTS, THIS PRODUCT HAS BEEN  
PROVEN TO PROVIDE THE HIGHEST LEVEL OF IIC SOUND ISOLATION IN THE INDUSTRY.

### SAMPLE RATINGS

IIC 72, STC 72: WOOD FLOORING, 8" CONCRETE SLAB, SUSPENDED CEILING  
IIC 54, STC 53: WOOD FLOORING, 6" CONCRETE SLAB, NO CEILING

### DIMENSIONS

THICKNESS: 2MM | WIDTH: 48IN | LENGTH 75 IN | WEIGH: 120LBS  
300 SF PER ROLL  
TYPE A HARDNESS: 40 DUROMETER

FOR MORE INFORMATION  
VISIT [WWW.PIDFLOORS.COM](http://WWW.PIDFLOORS.COM) OR CALL 212.337.3433