

PID FLOORS

HARDWOOD FLOORING SHOWROOMS

5 MM RECYCLED RUBBER UNDERLAYMENT



SKU RRU05

PERFORMANCE ATTRIBUTES

COMPATIBLE WITH MOST FLOOR FINISHES INCLUDING:
HARDWOOD, ENGINEERED WOOD, LAMINATE, LVT, AND CARPET

EASY INSTALLATION | MADE IN AMERICA FROM 92% RECYCLED RUBBER
CAN BE THIN-SET TO TILE OR STONE (UP TO 12 MM) PER ASTM C627
EARNS UP TO 9 LEED POINTS | COMPATIBLE WITH RADIANT HEATING SYSTEMS PROTECTS CERAMIC
TILE, PORCELAIN, AND STONE FROM SUBSTRATE CRACKS
RATED "LIGHT COMMERCIAL" BY THE TILE COUNCIL OF NORTH AMERICA
PASSES VOC IAQ TEST (ASTM D5116)

ACOUSTICS

YIELDS EXCEPTIONAL IMPACT SOUND INSULATION RESULTS, EVEN UNDER
HARD SURFACE FLOORING FOR CONCRETE OR WOOD-FRAMED CONSTRUCTION.

SAMPLE RATINGS

IIC 59: WOOD FLOORING, 8" CONCRETE SLAB, NO CEILING
IIC 58: WOOD FLOORING, 7" CONCRETE SLAB, NO CEILING

DIMENSIONS

THICKNESS: 5MM | WIDTH: 4FT | LENGTH 30FT | WEIGH: 100LBS
120 SF PER ROLL
TYPE A HARDNESS: 40 DUROMETER

FOR MORE INFORMATION
VISIT WWW.PIDFLOORS.COM OR CALL 212.337.3433